



Masonry Sealer & Stabiliser Data Sheet

Product Information

DESCRIPTION

An emulsion based, water dilutable scrim fixative and sealer for absorbent masonry surfaces.

USAGE/PURPOSE

Diluted (1-part to 3 parts water):

To seal masonry substrates prior to the application of water based finishes.

Undiluted: As a fixative for scrim along joints in board substrates (eg: plasterboard, cement particle board etc), prior to application of high build.

CHARACTERISTICS

Environmentally friendly, water-borne formulation
No fire or solvent vapour hazards during application or use

PERFORMANCE

Easy to use
Coverage: 20m² per litre (Diluted 1:3)
Reliable, effective results

Fast drying

COLOUR

Clear

ENVIRONMENTAL CONSIDERATIONS

Water-borne. Contains no added lead

PACKAGING

Can size: 5 litres

Technical Specification

COMPOSITION

Water based resin dispersion

PROPERTIES

VOC content: 0g/l

Cat. H: 50g/l (2007)/30g/l (2010)

Surface Preparation

Ensure surfaces are clean, firm and dry.

Application

METHOD

Apply by brush or roller.

THINNING

For fixing scrim: Do not thin.

For sealing masonry substrates: Dilute with water, 1 part Masonry Sealer to 3 parts water.

COVERAGE

Undiluted: Will fix approx. 50 linear metres of SCRIM per litre

Diluted: 1 litre (*diluted mixture*) will cover approx. 20m²

DRYING TIME

Approx. 3 hours, depending upon atmospheric conditions.

CLEANING

Clean all brushes, rollers and associated equipment with water immediately after use.

LIMITATIONS

DO NOT apply

- outside the temperature range 5-28°C
- when the temperature is likely to fall below 5°C within 2 hours
- if rain is likely within 4 hours

Health & Safety Notes

Detailed information and guidance is provided in **Material Safety Data Sheet:**

The following represents important selected information only

Ensure good ventilation during application and drying

Avoid contact with eyes and skin

In case of contact with eyes:

Rinse immediately with plenty of water and seek medical advice

In case of contact with skin:

Wash immediately with plenty of soap & water or a proprietary skin cleanser

Keep out of reach of children

ENVIRONMENTAL

The product and its container must be disposed of in a safe way

Do not empty into drains or watercourses.

Local Authorities have special facilities for the disposal of Paint materials.

Contractor: Use a paints recycling company to dispose of cans. Call our office for guidance on any disposal questions.

STORAGE

Store in secure, dry conditions at temperature between 5° and 28°C. Protect from frost. Containers should be kept closed during storage. Avoid spillage and contamination. Do not empty into drains and water courses.

SHELF LIFE

1 year in original, unopened container, if stored in accordance with recommendations above.

Specification

Fully written model propriety specifications for Proud Paints products are available from our Technical Services Department.



QUALITY CONTROL

All Proud Paints products are checked before release using the latest techniques to ensure controlled, consistent high quality.

Manufacturing Information

Manufactured under a quality system approved by the BSI to ISO 9001 – 2008.



Additional Information

TECHNICAL ASSISTANCE

For further information, advice or guidance regarding any aspect of Proud Paints products, please contact the Technical Services Department at the address below.

WARRANTY

As Proud Paints has no direct control over the methods employed by the user in applying its products, any warranty either written or implied, is given in good faith and can only cover the material itself.